

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

IN THE CLAIMS:

Please amend claims 1-14 as follows and add new claims 15-20. The following listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (Currently Amended). A radio communication system comprising:

a primary station, ~~and~~

a plurality of secondary stations, ~~the system having~~

5 a communication channel between the primary station and a secondary station, the communication channel comprising an uplink control channel and a downlink control channel for the transmission of control information between the primary and secondary stations, and

10 a data channel for the transmission of data packets, ~~characterised in that~~ each of the primary and secondary stations ~~have~~ having traffic reduction means for reducing traffic in the uplink and downlink control channels, and control means for activating the traffic reduction means,

15 the control means activating the traffic reduction means after a first data transmission on the data channel to cause the

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

uplink and downlink control channels to enter into a dormant state during which control information is transmitted on the uplink and downlink control channels,

- 20 the traffic reduction means being arranged to cause transmission of a reduced amount of control information on the uplink and downlink control channels while the uplink and downlink control channels are in the dormant state than the amount of control information transmitted on the uplink and  
25 downlink control channels during transmission of data packets on the data channel.

Claim 2 (Currently Amended). A system as claimed in claim 1, ~~characterised in that~~ wherein the control means activates the traffic reduction means after a predetermined period has passed without transmission of a data packet on the data channel after  
5 the first data transmission.

Claim 3 (Currently Amended). A system as claimed in claim 2, ~~characterised in that the traffic reduction means comprises means for transmitting a reduced amount of control information compared to that transmitted during transmission of data packets~~  
5 1, wherein the control means activates the traffic reduction means immediately after the first data transmission when the

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

control means determines that no additional data transmission is currently available for transmission.

Claim 4 (Currently Amended). A system as claimed in ~~any~~  
~~one of claims claim 1 to 3, characterised in that~~ wherein the  
traffic reduction means are arranged to transmit control  
information is transmitted on the uplink and downlink control  
5 channels in allocated time slots [[,]] and ~~in that the traffic~~  
~~reduction means operates~~ operate to transmit control information  
in one out of every N available slots when the uplink and  
downlink control channels are in the dormant state, where N is an  
integer greater than 1.

Claim 5 (Currently Amended). A system as claimed in claim  
1, ~~characterised in that~~ wherein the traffic reduction means  
~~comprises means for interrupting~~ are arranged to interrupt  
transmission of the uplink and downlink control channels after a  
5 time period has elapsed without transmission of a data packet on  
the data channel while the uplink and downlink control channels  
are in the dormant state.

Claim 6 (Currently Amended). A primary station for use in a  
radio communication system having a communication channel between  
the primary station and a secondary station, the communication

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

channel comprising an uplink and a downlink control channel for  
5 the transmission of control information between the primary  
station and the secondary station, and a data channel for the  
transmission of data packets, ~~characterised in that~~ the primary  
station comprising:

traffic reduction means ~~are provided~~ for reducing traffic in  
10 the downlink control channel, and

control means ~~are provided~~ for activating the traffic  
reduction means,

the control means activating the traffic reduction means  
after a first data transmission on the data channel to cause the  
15 uplink and downlink control channels to enter into a dormant  
state during which control information is transmitted on the  
uplink and downlink control channels,

the traffic reduction means being arranged to cause  
transmission of a reduced amount of control information on the  
20 uplink and downlink control channels while the uplink and  
downlink control channels are in the dormant state than the  
amount of control information transmitted on the uplink and  
downlink control channels during transmission of data packets on  
the data channel.

Claim 7 (Currently Amended). A primary station as claimed  
in claim 6, ~~characterised in that~~ wherein the control means

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

activates the traffic reduction means after a predetermined  
period has passed without transmission of a data packet on the  
5 data channel after the first data transmission.

Claim 8 (Currently Amended). A primary station as claimed  
in claim 6 ~~or 7, characterised in that~~ wherein the traffic  
reduction means are arranged to transmit control information ~~is~~  
~~transmitted~~ on the uplink and downlink control channels in  
5 allocated time slots [[,]] and ~~in that the traffic reduction~~  
~~means comprises means for transmitting a reduced amount of~~  
~~control information compared to that transmitted during~~  
~~transmission of data packets by transmitting~~ operate to transmit  
control information in one out of every N available slots when  
10 the uplink and downlink control channels are in the dormant  
state, where N is an integer greater than 1.

Claim 9 (Currently Amended). A secondary station for use in  
a radio communication system having a communication channel  
between the secondary station and a primary station, the  
communication channel comprising an uplink and a downlink control  
5 channel for the transmission of control information between the  
primary station and the secondary station, and a data channel for  
the transmission of data packets, ~~characterised in that~~ the  
secondary station comprising:

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

traffic reduction means ~~are provided~~ for reducing traffic in  
10 the uplink control channel, and

control means ~~are provided~~ for activating the traffic  
reduction means,

the control means activating the traffic reduction means  
after a first data transmission on the data channel to cause the  
15 uplink and downlink control channels to enter into a dormant  
state during which control information is transmitted on the  
uplink and downlink control channels,

the traffic reduction means being arranged to cause  
transmission of a reduced amount of control information on the  
20 uplink and downlink control channels while the uplink and  
downlink control channels are in the dormant state than the  
amount of control information transmitted on the uplink and  
downlink control channels during transmission of data packets on  
the data channel.

Claim 10 (Currently Amended). A secondary station as  
claimed in claim 9, ~~characterised in that~~ wherein the control  
means activates the traffic reduction means after a predetermined  
period has passed without transmission of a data packet on the  
5 data channel after the first data transmission.

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

Claim 11 (Currently Amended). A secondary station as claimed in claim 9 ~~or 10, characterised in that~~ wherein the traffic reduction means are arranged to transmit control information ~~is transmitted~~ in allocated time slots [[,]] and ~~in~~  
5 ~~that the traffic reduction means comprises means for transmitting a reduced amount of control information compared to that transmitted during transmission of data packets by transmitting~~  
operate to transmit control information in one out of every N available slots when the uplink and downlink control channels are  
10 in the dormant state, where N is an integer greater than 1.

Claim 12 (Currently Amended). A method of operating a radio communication system comprising a primary station and a plurality of secondary stations, the system having a communication channel between the primary station and a secondary station, the  
5 communication channel comprising an uplink and a downlink control channel for the transmission of control information between the primary station and the secondary station, and a data channel for the transmission of datapackets, ~~characterised by the primary and secondary stations being able to reduce traffic in the uplink~~  
10 ~~and downlink control channels~~ the method comprising:

entering the uplink and downlink control channel into a dormant state after a first data transmission on the data channel;

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

- transmitting control information on the uplink and downlink
- 15 control channels during transmission of data packets; and
- transmitting an amount of control information on the uplink  
and downlink control channels while the uplink and downlink  
control channels are in the dormant state which is less than the  
amount of control information transmitted on the uplink and
- 20 downlink control channels during transmission of data packets on  
the data channel.

Claim 13 (Currently Amended). A method as claimed in claim  
12, ~~characterised by~~ wherein the uplink and downlink control  
channels enter into the dormant state and the reduction in  
traffic in transmission of control information on the uplink and

5 downlink control channels being is initiated after a  
predetermined period has passed without transmission of a data  
packet on the data channel after the first data transmission.

Claim 14 (Currently Amended). A method as claimed in claim  
12 ~~or 13, characterised by~~ wherein control information being is  
transmitted in allocated time slots, and by the reduction in  
traffic including a reduction in the amount of control

5 information transmitted while the uplink and downlink control  
channels are in the dormant state compared to that transmitted  
during transmission of data packets is realized by transmitting



Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

control information in one out of every N available slots while  
the uplink and downlink control channels are in the dormant  
10 state, where N is an integer greater than 1.

Claim 15 (New). A system as claimed in claim 2, wherein the  
traffic reduction means are arranged to transmit control  
information on the uplink and downlink control channels in  
allocated time slots and operate to transmit control information  
5 in one out of every N available slots when the uplink and  
downlink control channels are in the dormant state, where N is an  
integer greater than 1.

Claim 16 (New). A system as claimed in claim 3, wherein the  
traffic reduction means are arranged to transmit control  
information on the uplink and downlink control channels in  
allocated time slots and operate to transmit control information  
5 in one out of every N available slots when the uplink and  
downlink control channels are in the dormant state, where N is an  
integer greater than 1.

Claim 17 (New). A primary station as claimed in claim 7,  
wherein the traffic reduction means are arranged to transmit  
control information on the uplink and downlink control channels  
in allocated time slots and operate to transmit control

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

- 5 information in one out of every N available slots when the uplink and downlink control channels are in the dormant state, where N is an integer greater than 1.

Claim 18 (New). A secondary station as claimed in claim 10, wherein the traffic reduction means are arranged to transmit control information in allocated time slots and operate to transmit control information in one out of every N available  
5 slots when the uplink and downlink control channels are in the dormant state, where N is an integer greater than 1.

Claim 19 (New). A method as claimed in claim 13, wherein control information is transmitted in allocated time slots, and the reduction in the amount of control information transmitted while the uplink and downlink control channels are in the dormant  
5 state compared to that transmitted during transmission of data packets is realized by transmitting control information in one out of every N available slots while the uplink and downlink control channels are in the dormant state, where N is an integer greater than 1.

Claim 20 (New). A method as claimed in claim 12, wherein the uplink and downlink control channels enter into the dormant state and the reduction in transmission of control information on

Appln. No. 10/694,555  
Amdt. dated December 19, 2005  
Reply to Office Action dated September 23, 2005

the uplink and downlink control channels is initiated immediately  
5 after the first data transmission when the control means  
determines that no additional data transmission is currently  
available for transmission.